

- Rubber Wheels:-



Wheels with rubber tyre and steel flanges or thermoplastic material centre ,available also with no marking grey rubber and with special rubber tyres antistatic ,oil proof ,super elastic and two-component mix .Wheels with black elastic rubber tyre and aluminium centre or polyamide 6 centre ,available also with grey no-marking rubber and blue cut resistant rubber .Wheels with mechanical cast iron centre or electro welded steel centre. These wheels are available in a range of diameters between mm 80 and mm 400 and combined with the various types of medium duty and heavy duty castors allow load capacities between kg 50 and kg 2500.



112



50 + 400

-20 + +80



Gres
Stoneware



Asfalto
Asphalt



Cemento
Concrete

Rubber wheels with steel flanges. Rubber ring. Flanges in zinc-chromium plated pressed steel. Hub on roller bearings, shielded ball bearings or self oiling bushes.



On request thread-guards available only with ball bearings.

MEDIUM DUTY CASTOR

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

80



80A



80B



80BI



80F



80BIS



103



80BISB



80BISBI



103B



103BI



103F



TRANSLATION NOT FOUND: TRANSLATE(EN, SPECIALI);

112AS



112AM



112AO



112SE



112BM

