

- Vibrator Hoses



CONCRETE VIBRATOR **Action Unit**

HV series concrete vibrator provides the best performance & dynamic power by special vibration system of pendulum type. The low rotational speed about 3,000 RPM provides less wear & tear for all rotating parts. Unique spring concept guarantees long durability.

- **Model: HV-38, 45, 50, 60**
Standard type and premium type available.

■ **Specification**

Model	Dia x L (mm)	Frequency (V.P.M)	Revolution (R.P.M)	Flexible Shaft	Weight (kg)	Motor Unit	Engine Unit
HV-38	38 x 445	12,000 ~14,000	3,000 ~3,600	6M (Standard) 4-7M (Available)	16	JGM-1(1HP) JGM-2(2HP) JGM-3(3HP)	3.5-6HP 3,600RPM Gasoline
HV-45	45 x 445				17		
HV-50	50 x 545				22		
HV-60	60 x 545				24		



» PENDULUM CONCRETE VIBRATOR / HOSE & FLEXIBLE SHAFT



Technical Data

Model	Vibrator Dia × Length	Frequency (vpm)	Revolution of Flexible Shaft (rpm)	Vibration Amplitude (mm)	Length of Flexible Shaft	Weight(kg) w/o drive unit	Electric Motor	Engine hp/rpm
JIV-32	32mm × 475mm	12,000	3,000	1.4	Standard:6m (4~7m Available)	15	1.0hp × 2p (JGM-1/15kg)	as required 3.5~6hp 3,600rpm Gasoline
JIV-38	38mm × 475mm			1.6		16		
JIV-45	45mm × 475mm	~	~	17				
JIV-50	50mm × 545mm	14,000	3,600	2.2		22	2hp × 2p(JGM-2/20kg)	
JIV-60	60mm × 545mm			2.4		24	3hp × 2p(JGM-3/21kg)	