

PUMPS:-

- Diesel Water Pumps



Diesel Water Pump



Product Model: KDP50B/L/LE

Model	KDP50B/L/LE
Suction/discharge port diameter [mm(in)]	50 (2")
Cont. capacity (L/min)	600
Cont. head [m(ft)]	18 (58.9)
Self-priming time (s/m)	70
Max suction head [m(ft)]	8.0 (26.16)
Rotation speed (rpm)	3600
Fuel consumption [g(ml)/kWh]	517 (707)

Overall dimension [mm(in)](L×W×H)	525×420×510
	(20.7×16.5×20.1)
Net weight [kg(lbs)]	35 (77)
Engine type	KD170F/FE
Rated power [KW(Hp)]	2.8 (3.83)
Rated rotation speed (rpm)	3600
Displacement [cm ³ (Cu-in)]	211 (12.87)
Starting system	B: small fuel tank;L: large fuel tank;E: electric start

Diesel Water Pump



Product Model: KDP80B/L/LE

Model	KDP80B/L/LE
Suction/discharge port diameter [mm(in)]	80 (3")
Cont. capacity (L/min)	1000
Cont. head [m(ft)]	19 (62.1)
Self-priming time (s/m)	120
Max suction head [m(ft)]	8.0 (26.16)
Rotation speed (rpm)	3600
Fuel consumption [g(ml)/kWh]	441 (603)
Overall dimension [mm(in)](L×W×H)	585×460×535
	(23×18.1×21.1)
Net weight [kg(lbs)]	52 (114)
Engine type	KD178F/FE
Rated power [KW(Hp)]	4.0 (5.5)
Rated rotation speed (rpm)	3600
Displacement [cm ³ (Cu-in)]	296 (18.06)
Starting system	B: small fuel tank; L: large fuel tank; E: electric start

Diesel Water Pump



Product Model: KDP100(A)B/L/LE

Model	KDP100(A)B/L/LE
Suction/discharge port diameter [mm(in)]	100 (4")
Cont. capacity (L/min)	1600
Cont. head [m(ft)]	21 (68.7)
Self-priming time (s/m)	180
Max suction head [m(ft)]	8.0 (26.16)
Rotation speed (rpm)	3600
Fuel consumption [g(ml)/kWh]	435 (595)
Overall dimension [mm(in)](LxWxH)	645x490x690
	(25.4x19.3x27.2)
Net weight [kg(lbs)]	69 (152)
Engine type	KD186F(A)/F(A)E
Rated power [KW(Hp)]	6.0 (8.2)
Rated rotation speed (rpm)	3600
Displacement [cm ³ (Cu-in)]	406 (24.76); A:418 (25.51)
Starting system	B: small fuel tank; L: large fuel tank; E: electric start