



- Fuel Pumps And Meters:-

Flow Meter



KOSHIN LTD.



**These pumps are not for use with liquids having a low flash-point, such as gasoline, etc.*

Powerful "FILL PUMP"

Only 2 Minutes to Empty 200 L Drum (FR-200)

- Two stage system of axial flow vane and spiral vane result in an excellent flow rate.

Specifications

Model		FA-100	FD-24	FD-12	FR-200		
P U M P	Connection Dia	20 mm (3/4")			32mm (1 1/4")		
	Connection Thread	Inner Pipe Thread					
	Total Head	7 m (23 ft)		6 m (19.5 ft)	11 m (36 ft)		
P	Delivery Volume	50 L/min (13 USG/min)		40 L/min (11 USG/min)	110 L/min (29 USG/min)		
		(Kerosene, Light Oil)		(Kerosene, Light Oil)	(Kerosene, Diesel)		
M O T O R	Type	Enclosed Fan-Cooled Commutator			Fan-Cooled Commutator		
	Voltage	AC 110V	AC 220V -240V	DC 24V	DV 12V	AC 110V	AC 220V -240V
	Rated Current	2 A	1 A	7 A	14 A	5 A	2.5 A
	Power	100 W	90 W		80 W	200 W	
	Revolution	7500 rpm	7300 rpm		7000 rpm	6200rpm	
	Rating	Continuous					
	Power cord	5 m (16 ft)					
	Delivery Hose	2m Oil-Proof Rubber Hose					
	Gross Weight	20 kg			30 kg		
	Dimensions LxWxH (mm)	1228 x 291 x 172			1290 x 490 x 205		
Packint Unit	2						

ALFANOOS