

PUMPS:-

-Gasoline Water Pumps



KOSHIN LTD.



SEH-50X



SEH-80X

Complete Range of Water Pumps Powered by Honda Engine

- Highly effective mechanical seal made with special carbon ceramics provides extra durability.
- Entire unit is protected by sturdy rollover pipe frame.
- Strong and lightweight die-cast aluminum pump.

Applications

- Sprinkling for field irrigation.
- Irrigation of paddy fields.
- Orchard cultivation.
- Pumping water from wells.
- Feeding or draining water to/from ponds or troughs.
- Feeding or draining water on fish farms.
- Washing cattle, barns or agricultural tools.
- Feeding water into water reservoirs.

Specifications

Model		SEH-50X		
P U M P	Connection Dia	50 mm (2")		
	Connection Thread	Outer Pipe Thread		
	Total Head	30 m (98 ft)		
	Delivery Volume	600 L/min (158 USG/min)		
	Max. Suction Head	8 m (26 ft)		
E N G I N E	Type	Forced Air-cooled 4-stroke Gasoline Engine		
	Model	Honda GX120	Honda G200	
	Exhaust Volume	118 cc	197 cc	
	Output	Rated Power	2.1 kW (2.9 PS) / 3600 rpm	2.8 kW (3.8 PS) / 3600 rpm
		Max. Power	2.6 kW (3.5 PS) / 3600 rpm	3.7 kW (5.0 PS) / 3600 rpm
	Fuel	Automotive Unleaded Gasoline		
	Fuel Tank Capacity	2 L	4.3 L	
	Continuous Operating Time	Approx. 2 hrs	Approx. 3 hrs	
Starting Method	Recoil Starter			
Standard Accessories	1 Strainer, 2 Hose Couplings, 3 Hose Bands, 1 Engine Tool Set			
Gross Weight	24 kg	29 kg		
Dimensions LxWxH (mm)	493 x 377 x 415	527 x 429 x 535		
Packing Unit	1			

Model		SEH-80X		SEH-100X		
P U M P	Connection Dia	80 mm (3")		100 mm (4")		
	Connection Thread	Outer Pipe Thread				
	Total Head	26 m (85 ft)		28 m (92 ft)		
	Delivery Volume	930 L/min (246 USG/min)	970 L/min (256 USG/min)	1450 L/min (383 USG/min)		
		Max. Suction Head				
E N G I N E	Type	Forced Air-cooled 4-stroke Gasoline Engine				
	Model	Honda GX160	Honda G200	Honda GX240		
	Exhaust Volume	163 cc	197 cc	242 cc		
	Rated Output	2.9 kW (3.9 PS) / 3600 rpm	2.8 kW (3.8 PS) / 3600 rpm	4.4 kW (6.0 PS) / 3600 rpm		
	Max. Output	3.6 kW (4.9 PS) / 3600 rpm	3.7 kW (5.0 PS) / 3600 rpm	5.3 kW (7.2 PS) / 3600 rpm		
	Fuel	Automotive Unleaded Gasoline				
	Fuel Tank Capacity	3.1 L	4.3 L	5.3 L		
	Continuous Operating Time	Approx. 2 hrs 10 min	Approx. 3 hrs	Approx. 2 hrs 30 min		
Starting Method	Recoil Starter					
Standard Accessories	1 Strainer, 2 Hose Couplings, 3 Hose Bands, 1 Engine Tool Set					
Gross Weight	34 kg	32 kg	59 kg			
Dimensions LxWxH (mm)	530 x 399 x 473	527 x 429 x 535	680 x 487 x 684			
Packing Unit	1					