

- Air Conditioning Equipments:-

Manifold Gauge



R12, R22, R502 BRASS MANIFOLD



- Heavy duty forged brass body.
- Large all metal handles are angled for ease of operation.
- Free-floating piston type valves reduce o-ring wear.
- Hose holder for convenient storage.
- Silicone dampened gauges smooth out needle movement.
- Gauges can be easily recalibrated in the field to maintain accuracy.
- Models available for various types of refrigerants.

- R12, R22, and R502 2-way manifold gauge sets with hoses packaged in clamshells.
- Hose connections are 1/4" SAE. Gauges are 2 1/2" or 3 1/8" in PSI & °F.

HOSE LENGTH (SET OF 3)	STANDARD HOSES STANDARD FITTINGS		STANDARD HOSES AUTO SHUT-OFF VALVES		NYLON BARRIER HOSES STANDARD FITTINGS		NYLON BARRIER HOSES AUTO SHUT- OFF VALVES		NYLON BARRIER HOSES MANUAL BALL VALVES	
	2-1/2"	3-1/8"	2-1/2"	3-1/8"	2-1/2"	3-1/8"	2-1/2"	3-1/8"	2-1/2"	3-1/8"
GAUGE SIZE										
36"	33636	33136	35636	35136	36636	36136	37636	37136	32636	32136
60"	33661	33161	35661	35161	36661	36161	37661	37161	32661	32161
72"	33772	33172	35772	35172	36772	36172	37772	37172	32772	32172

To order manifolds with shock-resistant gauge protectors, simply place a "-G" after the part number. (2 1/2" only)