

- Oil Can:-



Technical data

Volume of container (ml):	350
material of container:	steel
lacquering container:	red RAL 3000
material of pump:	Polyethylene
length of spout (mm):	135
material of spout:	Aluminium
Height (mm):	120
Base LxB (mm):	145 x 85
Weight (kg):	0,225

Specification

- angled spout ALU ([01 071](#))
- angled spout enables lubricating in difficult to access locations
- Single-acting plastic pump (EWKP)
- Robust pump provides trickle feed supply
- All valves are ball valve type
- High surface quality, lacquered with environment-friendly water based paint

Special notes

Ergonomic design

Packaging

Dimensions LxWxH (mm): 340x230x120

weight including package (kg): 1,52

Packing unit: 6.0



Technical data

Volume of container (ml):	250
material of container:	steel
lacquering container:	Red RAL3000
material of pump:	Polyethylene
length of spout (mm):	135
material of spout:	Aluminium
Height (mm):	120
Base LxB (mm):	135 x 70
Weight (kg):	0,21

Specification

- angled spout ALU ([01 071](#))
- angled spout enables lubricating in difficult to access locations
- Single-acting plastic pump (EWKP)
- Robust pump provides trickle feed supply
- All valves are ball valve type
- High surface quality, lacquered with environment-friendly water based paint

Special notes

Ergonomic design

Packaging

Dimensions LxWxH (mm): 335x230x120

weight including package (kg): 1,43

Packing unit:



Technical data

Volume of container (ml):	250
material of container:	steel
lacquering container:	blue,RAL5010
material of pump:	Brass
length of spout (mm):	135
material of spout:	Aluminium
length superflex spout:	210
material of flex spout:	PVC
Height (mm):	110
Base LxB (mm):	135 x 70
Weight (kg):	0,24

Specification

- angled spout ALU ([01 071](#))
- angled spout enables lubricating in difficult to access locations
- Superflex spout, transparent ([01 130](#))
- Single-acting brass pump (EWMP)
- Robust pump provides trickle feed supply
- All valves are ball valve type
- High surface quality, lacquered with environment-friendly water based paint

Special notes

Ergonomic design

Packaging

Dimensions LxWxH (mm): 335x230x120

weight including package (kg): 1,6

Packing unit: 6.0