

## - Air Operated Oil Pump:-



### **PM2 OIL PUMP, PRESSURE RATIO 1:1 - 200 l (55 gal) drum**

Double acting air operated low pressure pumps for transferring lubricants and other non-corrosive fluids. Pumps include height adjustable bung adaptor 2" BSP (M) for tank or drum mounting.

#### Products handled:

- Synthetic and mineral based lubricants.
- Transmission Fluid.
- Hydraulic oil.
- Diesel.
- Grease up to NLGI-2 (long pump only).

#### Markets

- Vehicle maintenance centres.
- Fleet service facilities.
- Manufacturing plants.
- Agriculture.
- Marine.
- Mining and construction.



## PumpMaster 2 pump connection kit

Pump connection kit. For PM2 3:1 pumps

### Componentes opcionales:

- 239000 Double male thread connection adaptors (1/4" BSPT-MM)
- 240500 Combined air filter, regulator, Ø 1/4" , 0 to 12 bar.
- 360150 Pump pulsation damper
- 609007 Pressure relief valve.
- 950300 Oil valve - 1/2" BSP (FF) - 65 bar (930 psi)



## **PM4 OIL PUMP, PRESSURE RATIO 3:1 - Wall mounted, stub pump**

Double acting air operated medium pressure and high volume pumps for dispensing lubricants in medium size installations including multiple dispensing points with simultaneous operation. Pumps are capable of pumping all types of lubricants, even those of high viscosity. Pumps include height adjustable bung adaptor 2" BSP (M) for drum and tank mounting and a built in port for connecting a pressure relief valve (PN609007).

### **PRODUCTS HANDLED**

- Synthetic and mineral based lubricants.
- Gear oil.
- Hydraulic oil.
- Transmission fluid.

### **MARKETS**

- Vehicle maintenance centres.
- Fleet service facilities.
- Manufacturing plants.
- Agriculture.
- Mining and construction.
- Lube tracks.
- Marine.