



- Fuel Pumps And Meters:-

Oil Dispensing Nozzle (Manual And Automatic)



PM4 OIL PUMP, PRESSURE RATIO 3:1 - Wall mounted, stub pump

Double acting air operated medium pressure and high volume pumps for dispensing lubricants in medium size installations including multiple dispensing points with simultaneous operation. Pumps are capable of pumping all types of lubricants, even those of high viscosity. Pumps include height adjustable bung adaptor 2" BSP (M) for drum and tank mounting and a built in port for connecting a pressure relief valve (PN609007).

PRODUCTS HANDLED

- Synthetic and mineral based lubricants.
- Gear oil.
- Hydraulic oil.
- Transmission fluid.

MARKETS

- Vehicle maintenance centres.
- Fleet service facilities.
- Manufacturing plants.

Agriculture.
Mining and construction.
Lube tracks.
Marine.



PumpMaster 3, 55:1 pressure ratio grease pump - 12,5-20 kg (40 lb) pails

Double acting air operated pumps for high pressure greasing. Recommended use in mobile units and single point dispensing units when the hose reel is connected directly to the pump outlet.

Typically used in workshops, service stations, fleet maintenance in mining, agriculture, armed forces, construction, trains, etc.

Pumps include height adjustable bung adaptor.

Pressure ratio: 55:1

Pump tube diameter: 26 mm (approx. 1")

Air piston diameter: 70 mm (approx. 3")

Air piston stroke: 35 mm (1,5")

Maximum free flow capacity: 600 gr/min (ounces / min)

Minimum air pressure: 3 bar (42 psi)

Maximum air pressure: 10 bar (140 psi)

Maximum fluid pressure: 550 bar (7.700 psi)

Air inlet: 1/4" BSPT (F)

Fluid outlet: 1/4" BSP (F)