

- Waste Oil Equipment:-



Mobile waste oil receiver - 100 litres (pump discharge)

The unit is discharged with a 1:1 pressure ratio pump, located at the back of the unit, through a 1.5 m discharge hose with a dry break quick coupler.

100 litres (26 US gallon) capacity, with side level gauge.

Large tray for tools, washers, filters, etc. on top of the tank.

One piece molded spoiler for securing the discharge hose in pressure discharge models.

Two reinforced casters and two reinforced wheels.

Composite and steel telescopic collection bowl, with 360° positionable oversized extension for wider reach. Anti-splash grid that can hold used filters for draining.

Steel tank and collection bowl with epoxy powder coating.



Mobile waste oil suction unit - 100 litres (with transparent chamber)

Includes a 10 litres transparent chamber that can be used as vacuum reservoir and allows an immediate inspection of the extracted waste oil.

100 litres (26 US gallon) capacity, with side level gauge.

Large tray for tools, washers, filters, etc. on top of the tank, with special holders for suction connectors.

One piece moulded spoiler for securing the discharge hose.

Two reinforced castors and two reinforced wheels.

High performance and low noise vacuum pump.

Complete suction canes and adapters kit with holder. Holder can be removed to clean it.

Steel tank with epoxy powder coating.