

- Gasoline Generator





Туре	Brushless, Self- Exciting, 2-Pole, Single Phase
Voltage Regulator	Condenser
Frequency	60 Hz
Max Output	2,900 Watts
Rated Output	2,400 Watts
Amps Rated 120V	20
12V DC Charging Amps	8.3 (100W)
Voltage AC	120V
Voltage DC	12V
dbA Rating	68 dbA
Circuit Breaker Protection	GFCI Breaker
Engine Model	EG17-6.0 HP

Engine Type	OHC, 4-Cycle, Air Cooled Gasoline	
Fuel	Gasoline	
Fuel Capacity US Gal.	4.4	
Continuous Hours	10.5	
Starter Type	Recoil	
Length inches	27	
Width inches	17	
Height inches	19	
Dry Wt. Ib	106	
Outlets—GFCI 120V Duplex	1	



	Phase
Voltage Regulator	Condenser
Frequency	60 Hz
Max Output	3,600 Watts
Rated Output	3,000 Watts
Amps Rated 120V/240V	25 / 12.5
12V DC Charging Amps	8.3 (100W)
Voltage AC	120V / 240V
Voltage DC	12V
dbA Rating	71 dbA
Circuit Breaker Protection	GFCI Breaker
Engine Model	EX21-7.0 HP
Engine Type	OHC, 4-Cycle, Air Cooled Gasoline
Fuel	Gasoline
Fuel Capacity US Gal.	4.4
Continuous Hours	8.4
Starter Type	Recoil
Length inches	24
Width inches	18
Height inches	20
Dry Wt. Ib	119
Outlets—GFCI 120V Duplex	1
Outlets—30amp 120V Twistlock	1
Outlets—30amp 120/240V Twistlock	1





RGX4800 STANDARD SPECIFICATIONS	
Туре	Brushless, Self- Exciting, 2-Pole, Single Phase
Voltage Regulator	Condenser
Frequency	60 Hz
Max Output	4,800 Watts
Rated Output	4,100 Watts
Amps Rated 120V/240V	34/17
12V DC Charging Amps	8.3 (100W)
Voltage AC	120V / 240V
Voltage DC	12V
dbA Rating	72 dbA
Circuit Breaker Protection	GFCI Breaker
Engine Model	EX27-9.0 HP
Engine Type	OHC, 4-Cycle, Air Cooled Gasoline
Fuel	Gasoline
Fuel Capacity US Gal.	4.4
Continuous Hours	6
Starter Type	Recoil
Length inches	26
Width inches	21
Height inches	22
Dry Wt. Ib	154
Outlets—GFCI 120V Duplex	1
Outlets—30amp 120V Twistlock	1
Outlets—30amp 120V/240V Twistlock	1